



SMOKE GUARD® *system*

SG Draft

Fixed Draft Curtain



System Description. **SG Draft** is a cost-effective, static curtain strategy for warehouses and manufacturing environments, used in both sprinklered and non-sprinklered buildings for automatic smoke removal. Draft curtains channel the ceiling jet away from the fire and out of the building via roof vents to remove the smoke or delay sprinkler activation.

Description. **SG Draft** is a code-compliant, lightweight, fixed fabric curtain, semi-permanent or temporary, system for large vertical openings. The **SG Draft SGTex10** smoke curtain material is a glass filament fabric with a glass fiber material on one side.

Dimensions

- unlimited widths
- variable drop lengths

Code Compliance

- 2015/2018 IBC Section 910.2.1
- NFPA 409 Section 5.17
- NFPA 92 - Smoke Control Systems

Compliance and Performance Standards

- ASTM E 84 "Surface Burning Characteristics of Building Materials"
- ASTM E 136 Certified Fabric

Curtain Dimensions. **SG Draft** panels are manufactured in custom widths for ceiling spans of an unlimited width with a maximum drop length of 15 feet. Consult smokeguard.com or your local distributor for detailed information on this product.

Installation. All Smoke Guard products are to be installed by factory recognized installation personnel.



Designed, Assembled, and Tested in the USA





SMOKE GUARD® *system*

SG Draft Fixed Draft Curtain



Designed, 
Assembled and 
Tested in the USA 